



HIACE/ ACE

Valid from: November, 2023

GRADE	SFX	Body type	Engine	ccm	Power (HP/kW)	Torque (Nm)	Transmission	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
Delux	K3 - 202	Mini bus 15 seats	2.5 D-4D	2494	102/75	260	5 M/T	36,900	47,300
Delux plus	K6 - 222	Mini bus 14 seats	2.5 D-4D	2494	102/75	260	5 M/T	53,300	85,300
Delux plus ambulance- Basic	K6B-222	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	68,800	*-
Delux plus ambulance- Medium	K6M-222	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	72,200	*-
Delux plus ambulance- Advance	K6A-222	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	73,100	*-
Commuter	16 - 322	Mini bus 16 seats	2.8 D-4D	2755	102/75	260	6 M/T	63,600	81,100

EXTRAS	DELUXE	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
Metallic paint:	0		

• = Standard ○ = Option -= Not available 5 M/T = 5 speed manual transmission

STANDARD ROOF - STANDARD GRADE

Interior:

Seating capacity: total of 15 seats, 5 rows

Air conditioner (manual)

Clean air filter

Front and rear cooler and heater system

Power door lock (front, slide, back)

Radio AM/FM, MP3, CD

Auxiliary input USB

4 speakers (2 front, 2 rear)

Power windows, auto down for driver

Fabric seat material Dust protection

Glove box Floor mats

Exterior:

Mud guards (front and rear) Black front bumper

Black door handles

Quarter front and rear sliding windows (glass)

Deep grey rear glass

Luggage back door, lift up

Safety: ABS - Anti-lock Braking System Driver & passenger airbags (SRS)

High mount stop light, LED

2-point rear seatbelts Fire extinguisher

Technical:

Headlamp 2-bulb halogen

Steel wheels with covers

Tyre dimensions 195 R15C 15X6J

Spare tyre

Fuel tank capacity 70L

Curb weight: 1.835 kg

Gross weight: 3.050 kg

Pay load: 1.215 kg Overall width: 1.695 mm (1.880 mm for High roof)

Overall length. 4.695 mm (5.380 mm for High roof)

Overall height: 1.980 mm (2.285 mm for High roof)

Min. ground clearance: 185 mm Min. turning radius (tyre): 5.0 m (6.2 m for High roof)

Min. turning radius (body): 5.7 m (6.9 m for High roof)

HIGH ROOF - on top of standard roof

Interior:

Seating capacity: total of 14 seats, 5 rows Rear seats adjustments, semi reclining

Exterior:

Luggage back door, high opening damper

Safety:

Rear headrests 3-point rear seatbelts



LUSAKA CAIRO RD BRANCH Nothend Cairo road- Lusaka Tel: +260971 268 000

LUSAKA NANGWENYA BRANCH

Nangwenya Road- Lusaka Tel: +260971 268 000

KITWE COPPERBELT BRANCH Chingola Road- Kitwe Tel: +260971 260 000

LIVINGSTONE BRANCH Plot No. 699- Industrial Road- Livingstone Tel: +260971 268 000 SOLWEZI BRANCH Kansanshi Mine Road Tel: +260971 268 000

www.toyotazambia.co.zm contact-toyota-zambia@cfao.com website: e-mail:



Warranty is valid up to 5 years or 150,000 km for vehicle and 1 year or 30,000 km for conversions, whichever comes first. We reserve the right to alter any details of specifications and equipment without notice. No guarantee is given regarding the accuracy of information within this document. Vehicle body, specifications and trim colours might differ slightly from the data within this document. Please check model availability and full specification details with your Toyota dealer prior to ordering. We cannot accept contractual responsibility for your reliance on the information contained within this document.

HIACE







