



HIACE/ ACE

Valid from: 8th January 2026

GRADE	SFX	Body type	Engine	ccm	Power (HP/kW)	Torque (Nm)	Transmission	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
Panel Van	K0	Mini bus	2.5 D-4D	2494	102/75	260	5 M/T	37,100	55,600
Standard	K3	Mini bus 15 seats	2.5 D-4D	2494	102/75	260	5 M/T	38,600	49,600
High Roof	K6	Mini bus 14 seats	2.5 D-4D	2494	102/75	260	5 M/T	55,900	89,400
High roof panel van	K6P	Mini bus	2.5 D-4D	2494	102/75	260	5MT	57,700	86,900
Delux plus ambulance-Basic	K6B	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	71,100	~
Delux plus ambulance-Medium	K6M	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	75,400	~
Delux plus ambulance-Advance	K6A	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	74,500	~
Commuter	16	Mini bus 16 seats	2.8 D-4D	2755	102/75	260	6 M/T	65,800	84,000

EXTRAS	DELUXE	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
--------	--------	-------------------------------	------------------------

Metallic paint:

● = Standard ○ = Option – = Not available
5 M/T = 5 speed manual transmission

○

(USD) Prices are Indicative

STANDARD ROOF - STANDARD GRADE

Interior:

Seating capacity: total of 15 seats, 5 rows
Air conditioner (manual)
Clean air filter
Front and rear cooler and heater system
Power door lock (front, slide, back)
Radio AM/FM, MP3, CD
Auxiliary input USB
4 speakers (2 front, 2 rear)
Power windows, auto down for driver
Fabric seat material
Dust protection
Glove box
Floor mats

Exterior:

Mud guards (front and rear)
Black front bumper
Black door handles
Quarter front and rear sliding windows (glass)
Deep grey rear glass
Luggage back door, lift up

Safety:

ABS - Anti-lock Braking System
Driver & passenger airbags (SRS)
High mount stop light, LED
2-point rear seatbelts
Fire extinguisher

Technical:

Headlamp 2-bulb halogen
Steel wheels with covers
Tyre dimensions 195 R15C 15X6J
Spare tyre
Fuel tank capacity 70L
Curb weight: 1.835 kg
Gross weight: 3.050 kg
Pay load: 1.215 kg
Overall width: 1.695 mm (1.880 mm for High roof)
Overall length: 4.695 mm (5.380 mm for High roof)
Overall height: 1.980 mm (2.285 mm for High roof)
Min. ground clearance: 185 mm
Min. turning radius (tyre): 5.0 m (6.2 m for High roof)
Min. turning radius (body): 5.7 m (6.9 m for High roof)

HIGH ROOF - on top of standard roof

Interior:

Seating capacity: total of 14 seats, 5 rows
Rear seats adjustments, semi reclining

Exterior:

Luggage back door, high opening damper

Safety:

Rear headrests
3-point rear seatbelts



CONTACT US:

LUSAKA CAIRO RD BRANCH
Nothend Cairo road- Lusaka
Tel: +260971 268 000

KITWE COPPERBELT BRANCH
Chingola Road- Kitwe
Tel: +260971 260 000

SOLWEZI BRANCH
Kansanshi Mine Road
Tel: +260971 268 000

LUSAKA NANGWENYA BRANCH
Nangwenya Road- Lusaka
Tel: +260971 268 000

LIVINGSTONE BRANCH
Plot No. 699- Industrial Road- Livingstone
Tel: +260971 268 000

website: www.toyotazambia.co.zm
e-mail: contact-toyota-zambia@cfao.com



#REF!

HIACE

