



HIACE/ ACE

Indicative Price List in USD: Valid from 5th Feb 2026

GRADE	SFX	Body type	Engine	ccm	Power (HP/kW)	Torque (Nm)	Transmission	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
Panel Van	K0	Mini bus	2.5 D-4D	2494	102/75	260	5 M/T	38,300	57,200
Standard	K3	Mini bus 15 seats	2.5 D-4D	2494	102/75	260	5 M/T	39,900	51,200
High Roof	K6	Mini bus 14 seats	2.5 D-4D	2494	102/75	260	5 M/T	57,700	91,900
High roof panel van	K6P	Mini bus	2.5 D-4D	2494	102/75	260	5MT	59,400	89,200
Delux plus ambulance-Basic	K6B	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	73,200	*-
Delux plus ambulance-Medium	K6M	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	77,600	*-
Delux plus ambulance-Advance	K6A	Mini bus	2.5D-4D	2494	102/75	260	5 M/T	76,700	*-
Commuter	16	Mini bus 16 seats	2.8 D-4D	2755	102/75	260	6 M/T	67,400	86,000

EXTRAS	DELUXE	Duty and VAT Free Price (USD)	Duty paid (USD w. VAT)
Metallic paint:	o		

● = Standard ○ = Option -- = Not available
5 M/T = 5 speed manual transmission

STANDARD ROOF - STANDARD GRADE

Interior:

Seating capacity: total of 15 seats, 5 rows
Air conditioner (manual)
Clean air filter
Front and rear cooler and heater system
Power door lock (front, slide, back)
Radio AM/FM, MP3, CD
Auxiliary input USB
4 speakers (2 front, 2 rear)
Power windows, auto down for driver
Fabric seat material
Dust protection
Glove box
Floor mats

Exterior:

Mud guards (front and rear)
Black front bumper
Black door handles
Quarter front and rear sliding windows (glass)
Deep grey rear glass
Luggage back door, lift up

Safety:

ABS - Anti-lock Braking System
Driver & passenger airbags (SRS)
High mount stop light, LED
2-point rear seatbelts
Fire extinguisher

Technical:

Headlamp 2-bulb halogen
Steel wheels with covers
Tyre dimensions 195 R15C 15X6J
Spare tyre
Fuel tank capacity 70L
Curb weight: 1.835 kg
Gross weight: 3.050 kg
Pay load: 1.215 kg
Overall width: 1.695 mm (1.880 mm for High roof)
Overall length: 4.695 mm (5.380 mm for High roof)
Overall height: 1.980 mm (2.285 mm for High roof)
Min. ground clearance: 185 mm
Min. turning radius (tyre): 5.0 m (6.2 m for High roof)
Min. turning radius (body): 5.7 m (6.9 m for High roof)

HIGH ROOF - on top of standard roof

Interior:

Seating capacity: total of 14 seats, 5 rows
Rear seats adjustments, semi reclining

Exterior:

Luggage back door, high opening damper

Safety:

Rear headrests
3-point rear seatbelts



CONTACT US:

LUSAKA CAIRO RD BRANCH
Nothend Cairo road- Lusaka
Tel: +260971 268 000

KITWE COPPERBELT BRANCH
Chingola Road- Kitwe
Tel: +260971 260 000

SOLWEZI BRANCH
Kansanshi Mine Road
Tel: +260971 268 000

LUSAKA NANGWENYA BRANCH
Nangwenya Road- Lusaka
Tel: +260971 268 000

LIVINGSTONE BRANCH
Plot No. 699- Industrial Road- Livingstone
Tel: +260971 268 000

website: www.toyotazambia.co.zm
e-mail: contact-toyota-zambia@cfao.com



Warranty is valid up to 5 years or 150,000 km for vehicle and 1 year or 30,000 km for conversions, whichever comes first. We reserve the right to alter any details of specifications and equipment without notice. No guarantee is given regarding the accuracy of information within this document. Vehicle body, specifications and trim colours might differ slightly from the data within this document. Please check model availability and full specification details with your Toyota dealer prior to ordering. We cannot accept contractual responsibility for your reliance on the information contained within this document.

HIACE

